

Technical Datasheet



General description	
Technology	3D stereo vision / Edge computing with artificial intelligence (AI)
Environment	Indoor
Data storage	up to 3 years (depending on the number of counters)
Data privacy	4 privacy modes / data is only transmitted in text format and without any kind of personally identifiable information
Integration	API with Swagger documentation, data pushes, remote device management tool, count verification tool on-device

Electrical Characteristics	
Power supply	Power over Ethernet, Class 0 (IEEE 802.3af, nominal 48V)
Power consumption	Maximum 6.0 W, 0.125A

Environmental Conditions	
Required illumination	Minimum 2 lux
Operating temperature	0 °C to +45 °C / +32 °F to +113 °F
Storage temperature	Long-term storage (max. 6 months): +5 °C to +35 °C / +41 °F to +95 °F transport (< 1 month): -20 °C to +70 °C / -4 °F to +158 °F
Overheating protection	Automatically shuts down if internal temperature is higher than +79 °C / +174 °F
Relative Humidity	20 to 80 % (non-condensing)
Pollution degree	PD2 (acc. to IEC 62368)
Ingress Protection	IP40 (acc. to IEC 60529)
Shelf life	6 months

Technical Datasheet

Physical Interfaces	
Ethernet	IEEE 802.3ab 1000Base-T (Gigabit Ethernet)
Connector	RJ 45
Cable	Up to 100 m / 328 ft, min. Cat-5e (shielded) or higher
PoE Power source	Use Power supplies compliant with all locally applicable safety standards

Network Interfaces	
Supported protocols	IPv6, IPv4, DHCP, HTTPS and password-protected configuration access
Data push protocols	HTTP(S), FTP(S), SFTP, MQTT(S), TCP, UDP

Installation / Mounting	
Mounting options	Different mounting options available. Find more information in our accessory brochure.
Mounting height	PC2SE / PC2SE-L: 2.20 m to 6.00 m / 7.22 ft to 19.69 ft PC2SE-UL: 2.20 m to 3.50m / 7.22 ft to 11.48 ft Find more information in our selection guide to get an overview of the coverage.
Mounting angle (Tilt)	+/-15° in x-axis +/- 5° in y-axis
Grounding	Sensor grounding is optional. The use of shielded cables is recommended.

Mechanical Characteristics	
Weight (incl. Cover)	300 g / 0.66 lb
Weight (without Cover)	250 g / 0.55 lb
Dimensions (L x W x H)	Without plastic cover: 12.76 x 8.89 x 3.16 cm / 5.02 x 3.50 x 1.24 in With plastic cover: 13.02 x 9.32 x 3.28 cm / 5.13 x 3.67 x 1.29 in

Standards, approval, certificates	
Safety	IEC 62368-1 EN 62368-1
EMC	IEC 61326-1 EN 61326-1 CISPR 11 / EN 55011 CISPR 32 / EN 55032 CISPR 35 / EN 55035 FCC 47 CFR part 15 Edition ICES-001, Issue 5
Others	2011/65/EU (RoHS)